

ATX12V

Power Supply Design Addendum for 150 Watt PCI-Express* Power

Version 1.0

Revision History

Version	Release Date	Notes	
1.0	June 2004	<ul style="list-style-type: none">• First public release	

IMPORTANT INFORMATION AND DISCLAIMERS

INTEL CORPORATION (AND ANY CONTRIBUTOR) IS PROVIDING THIS INFORMATION AS A CONVENIENCE AND ACCORDINGLY MAKES NO WARRANTIES WITH REGARD TO THIS DOCUMENT OR PRODUCTS MADE IN CONFORMANCE WITH THIS DOCUMENT.

THIS DOCUMENT IS PROVIDED "AS IS" AND INTEL DISCLAIMS ALL EXPRESS AND IMPLIED WARRANTIES, INCLUDING THE WARRANTY OF MERCHANTABILITY AND FITNESS FOR PARTICULAR PURPOSE. IN ADDITION, INTEL (AND ANY CONTRIBUTOR) DOES NOT WARRANT OR REPRESENT THAT THIS DOCUMENT OR ANY PRODUCTS MADE IN CONFORMANCE WITH IT WILL OPERATE IN THE INTENDED MANNER, ARE FREE FROM ERRORS OR DEFECTS, OR ARE SAFE FOR USE FOR ITS INTENDED PURPOSE. ANY PERSON USING THIS DOCUMENT OR MAKING, USING, OR SELLING PRODUCTS IN CONFORMANCE WITH THIS DOCUMENT DOES SO AT HIS OR HER OWN RISK.

INTEL DISCLAIMS ALL LIABILITY ARISING FROM OR RELATED TO USE OR IMPLEMENTATION OF THE INFORMATION PROVIDED IN THIS DOCUMENT, INCLUDING LIABILITY FOR INFRINGEMENT OF ANY INTELLECTUAL PROPERTY RIGHTS RELATING TO THE INFORMATION OR THE IMPLEMENTATION OF INFORMATION IN THIS DOCUMENT. INTEL DOES NOT WARRANT OR REPRESENT THAT SUCH DEVICES OR IMPLEMENTATION WILL NOT INFRINGE SUCH RIGHTS.

INTEL IS NOT OBLIGATED TO PROVIDE ANY SUPPORT, INSTALLATION OR OTHER ASSISTANCE WITH REGARD TO THE INFORMATION OR PRODUCTS MADE IN ACCORDANCE WITH IT. THE INFORMATION IN THIS DOCUMENT IS SUBJECT TO CHANGE WITHOUT NOTICE.

THE INFORMATION REFERRED TO IN THIS DOCUMENT IS INTENDED FOR STANDARD COMMERCIAL USE ONLY. CUSTOMERS ARE SOLELY RESPONSIBLE FOR ASSESSING THE SUITABILITY OF THE INFORMATION FOR USE IN PARTICULAR APPLICATIONS. THE INFORMATION IS NOT INTENDED FOR USE IN CRITICAL CONTROL OR SAFETY SYSTEMS, MEDICAL OR LIFE SAVING APPLICATIONS, OR IN NUCLEAR FACILITY APPLICATIONS.

NO LICENSE, EXPRESS OR IMPLIED, BY ESTOPPEL OR OTHERWISE, TO ANY INTELLECTUAL PROPERTY RIGHTS IS GRANTED HEREIN.

Intel and Pentium are registered trademarks of Intel Corporation or its subsidiaries in the United States and other countries.

Other names and brands may be claimed as the property of others

Copyright © 2004 Intel Corporation.

Contents

1. Scope	4
2. Electrical	4
3. PCI-Express* Power Connector	5

Figures

Figure 1 Cross Loading Graph	5
Figure 2 Details of 2 x 3 PCI-Express* Graphics Power Connector (Molex* P/N 45559-002 or equivalent)	6

Tables

Table 1 Typical Power Distribution for ATX12V Configuration with support for 150W PCI-Express* Graphics	4
Table 2 Loading Table for Efficiency Measurements	5
Table 3 2 x3 PCI-Express* Graphics Power Connector.....	6

1. Scope

This addendum provides information for development of a power supply to support 150W PCI-Express* graphic card power requirements for a high end performance ATX system. Refer to *ATX12V Power Supply Design Guide* version 2.0 or greater for important details regarding the power supply.

2. Electrical

Table 1 Typical Power Distribution for ATX12V Configuration with support for 150W PCI-Express* Graphics

Output	Min. Current (amps)	Max. Current (amps)	Peak Current (amps)
+12 V1DC ^(1, 2)	1	18	
+12 V2DC ^(1, 2)	1	16	18
+5 VDC	0.3	25	
+3.3 VDC	0.5	20	
-12 VDC	0	0.3	
+5 VSB	0	2	2.5

Note:

Total 5V & 3.3V output power combined should not exceed 130 Watts

(1) 12V1DC should have separate current limit circuits to meet 240VA safety requirements

(2) 12V2DC supports processor VR and should have separate current limit

Figure 1 Cross Loading Graph




Table 2 Loading Table for Efficiency Measurements

400W (loading shown in Amps)						
Loading	+12V1	+12V2	+5V	+3.3V	-12V	+5Vsb
Full	16	14	9	11	0.3	1.0
Typical	9.5	6	3	5	0.1	1.0
Light	3	3	1	3	0.0	1.0

3. PCI-Express* Power Connector:

A 6 pin (2 x 3) Molex P/N 45559-0002 or equivalent connector is required in addition to standard ATX12V DC connectors. The details of the additional connector and its pin out are shown.

Figure 2 Details of 2 x 3 PCI-Express* Graphics Power Connector (Molex* P/N 45559-0002 or equivalent)




Table 3 2 x3 PCI-Express* Graphics Power Connector

Connector: Molex P/N 45559-0002 or equivalent
6 Connector Receptacle Housing Special Fit

Pin	Signal	Color
1	+12V1VDC	Yellow
2	+12V1VDC	Yellow
3	+12V1VDC	Yellow
4	GND	Black
5	GND	Black (Used to sense connector on Graphics Card)
6	GND	Black