



| REV. | REVISIONS | REC. | REV. | REVISIONS | REC. |
|------|---------------------------------|------|------|-----------|------|
| 1 | (B):10.0 ->10.2, (I):1.5 ->1.7. | | | | |
| 2 | ADD (J),(L),(K). | | | | |

| | | | | | |
|---|--------------|-----------------------|-----------------|--------------------|-------------------|
| DRAWN & DRAFTED BY CAO LI WEI | TOLERANCES | | ANGLE: | TITLE: | |
| | 0<L≤4 ±0.1 | COPLANRITY 0.1 MAX | ±1° | SMD BASE SM-CEF105 | |
| CHECKED & APPROVED BY LONG HONG JUN | 4<L≤16 ±0.2 | | UNIT: | BOBBIN MATERIAL: | UL REC. |
| | 16<L≤63 ±0.3 | MM | PHENOLIC PM9630 | UL 94V-0 | |
| PIN SHINE INDUSTRIAL CO., LTD. TEL:886-2-22990545 FAX:886-2-22990546 | | | ORIGIN: | PIN MATERIAL: | PIN TENSION LOAD: |
| | | | DG | PHOSPHOR BRONZE | |
| | | | DATE: | DRAWING NO. | REV. |
| | | | JUN.04 '2003 | SB-022 | 2 |