

A: 如何选定型号

TAJ B 335 M 016 R *

① ② ③ ④ ⑤ ⑥ ⑦

- ① 类型
- ② 外形尺寸: (见下表)
- ③ 电容值: 前面两位数字表示有效数字, 第三数字表示倍率 (即后面跟随0的个数)
- ④ 误差: K=±10%, M=±20%, J=±5%
- ⑤ 额定直流电压
- ⑥ 包装: R=7" 带式 and 卷式; S=13" 带式 and 卷式
- ⑦ 对于特殊要求来说, 可以增加附加的文字



B、外形尺寸: 毫米 (英寸)

代码	EIA 代码	L ±0.2(0.008)	V ±0.2(0.008) -0.1(0.004)	H ±0.2(0.008) -0.1(0.004)	W ±0.2(0.008)	A ±0.3(0.012) -0.2(0.008)	S Min
A	3216	3.2(0.126)	1.6(0.063)	1.6(0.063)	1.2(0.047)	0.8(0.031)	1.1(0.034)
B	3528	3.5(0.138)	2.8(0.110)	1.9(0.075)	2.2(0.087)	0.8(0.031)	1.4(0.055)
C	6032	6.0(0.236)	3.2(0.126)	2.6(0.102)	2.2(0.087)	1.3(0.051)	2.9(0.114)
D	7343	7.3(0.287)	4.3(0.169)	2.9(0.114)	2.4(0.094)	1.3(0.051)	4.4(0.173)
E	7343H	7.3(0.287)	4.3(0.169)	4.1(0.162)	2.4(0.094)	1.3(0.051)	4.4(0.173)
M	4726	4.7(0.185)	2.6(0.102)	2.1(0.083)	1.4(0.055)	0.8(0.031)	2.7(0.106)
N	5846	5.8(0.228)	4.6(0.181)	3.2(0.126)	2.4(0.094)	1.3(0.051)	2.8(0.110)

C、标准包装

	带式 and 卷式	
	7"	13"
A	2000	8000
B	2000	8000
C	500	3000
D	500	2500
E	400	1500
M	1500	5000
N	500	2500

D、容量范围

电容和电压范围 (字母表示外形尺寸)									
电容	在 85°C 时的额定直流电压 (V _r)								
		4V	6.3V	10V	16V	20V	25V	35V	50V
0.1	104								
0.15	154								
0.22	224								A
0.33	334								A
0.47	474								
0.68	684								
1.0	105						A	A	
1.5	155					A	B	BM	C
2.2	225				A	A	B	BM	
3.3	335			A	A	B	B	C	
4.7	475		A	A	A	B	C	C	
6.8	685	A	A	A	BA	B	C	C	D
10	106	A	A	BA	BA	C	C	D	
15	156	BA	B	BA	CB	C	D	D	
22	226	BA	BA	B	CB	C	D	E	
33	336	CB	CB	CB	C	D	E		
47	476	CB	CB	C	DC	E			
68	686	CB	B	DC	DD	E			
100	107	CB	DC	DC	ED				
150	157	DC	DC	ED	DE				
220	227	DC	EC	ED	E				
330	337	ED	ED	D	E				
470	477	DE	DE	DE					
680	687	DE	DE	E					
1000	108	E	E						

E、TAJ 系列

