



GE Lighting North America



Home Lighting | Business Lighting | Browse | Search | Help

| Specifier/OEM | Lighting Institute

| Where to Buy

| e-Catalog


| Contact Us

- ▾ Incandescent
- ▾ Halogen
- ▾ High Intensity Discharge
- ▾ Fluorescent

- ▣ Starcoat™ T8
- ▣ T8 Watt-Miser® (4', 8', XL)
- ▣ Starcoat™ XL Extra-Life
- ▣ F25T12 for T8 Ballasts
- ▣ T8 Ecolux® - TCLP Compliant
- ▣ T8 Ecolux® XL and SXL Extra-Life
- ▣ T8 Mod-U-line®
- ▣ 8' T8
- ▣ 8' T8 XL Extra Life
- ▣ 8' T8 HO
- ▣ F30T12
- ▣ F40 Ecolux® - TCLP Compliant
- ▣ F40 Mod-U-Line®
- ▣ F40 Standard
- ▣ F40 Watt-Miser®
- ▣ F40 XL Extra-Life
- ▣ F48" Utility Shoplight
- ▣ 8' Instant Start XL Extra-Life
- ▣ 8' Instant Start Watt-Miser®
- ▣ Instant Start
- ▣ T12 High Output Rapid Start
- ▣ T12 Very High Output (1500mA)
- ▣ Power Groove®
- ▣ Preheat
- ▣ Gold
- ▣ "All-Weather"
- ▣ Appliance
- ▣ Blacklight/Blacklight Blue
- ▣ Circline Lamps
- ▣ CovRguard™ Shatter Protected
- ▣ Grocery Display Lamps
- ▣ Diazo
- ▣ Cold Temperature
- ▣ Germicidal
- ▣ Plant and Aquarium/Terrarium
- ▣ T5 Rapid Start
- ▣ T5 Rapid Start HO
- ▣ Other

- ▾ Compact Fluorescent
- ▾ Stage/Studio
- ▾ Miniature/Sealed Beam
- ▾ Projection
- ▾ Merchandiser

Basic | LSB | Images | Right Light Options | **13748 - Instant Start Item Detail**



Subcategory	Instant Start
Product Code	13748
Description	F72T12/D
Watts	55
Lumens (Initial)	3800
Lumens (Mean)	3500
Average Rated Life	12000
Color Temperature (K)	6500
Color Rendering Index (Ra) CRI	75
Bulb Type	T12
Base Type	Single Pin (Fa8)
Nominal Length (In.)	72.0000
Nominal Length (mm)	1830.000
Sales Unit UPC	043168137485
Case UPC	043168137485
SCC	00043168137485
Govt. Nat'l Stock Number	6240002259702
Case Quantity	15
Additional Information	Daylight

LSB Data Available

[Return to product list](#)

Set the current view to the default view