

ZERO RECOVERY[®] RECTIFIERS

	V _{RRM} (V)	I _{F(AV)} (A)	V _{F(T_J= 25°C)}		V _{F(T_J= 175°C)}		T _{J(MAX)}	Package Type	
			Typ	Max	Typ	Max			
CSD10030A	300	10	1.2	1.4	1.4	1.8	175°C	TO-220-2	See Fig. 1
CSD20030D	300	20	1.2	1.4	1.4	1.8	175°C	TO-247-3	See Fig. 5
CSD01060A	600	1	1.6	1.8	2.0	2.4	175°C	TO-220-2	See Fig. 1
CSD01060E	600	1	1.6	1.8	2.0	2.4	175°C	DPAK	See Fig. 3
CSD04060A	600	4	1.5	1.8	2.0	2.4	175°C	TO-220-2	See Fig. 1
CSD04060B	600	4	1.5	1.8	2.0	2.4	175°C	TO-220-3	See Fig. 2
CSD04060E	600	4	1.5	1.8	2.0	2.4	175°C	DPAK	See Fig. 3
CSD06060A	600	6	1.6	1.8	1.9	2.4	175°C	TO-220-2	See Fig. 1
CSD06060B	600	6	1.6	1.8	1.9	2.4	175°C	TO-220-3	See Fig. 2
CSD06060G	600	6	1.6	1.8	1.9	2.4	175°C	D ² PAK	See Fig. 4
CSD10060A	600	10	1.5	1.8	2.0	2.4	175°C	TO-220-2	See Fig. 1
CSD10060G	600	10	1.5	1.8	2.0	2.4	175°C	D ² PAK	See Fig. 4
CSD20060D	600	20	1.5	1.8	2.0	2.4	175°C	TO-247-3	See Fig. 5
CSD05120A	1200	5	1.6	1.8	2.6	3.0	175°C	TO-220-2	See Fig. 1
CSD10120A	1200	10	1.6	1.8	2.5	3.0	175°C	TO-220-2	See Fig. 1
CSD10120D	1200	10	1.6	1.8	2.6	3.0	175°C	TO-247-3	See Fig. 5
CSD20120D	1200	20	1.6	1.8	2.5	3.0	175°C	TO-247-3	See Fig. 5

Fig. 1 TO-220-2




Fig. 2 TO-220-3




Fig. 3 DPAK



Fig. 4 D²PAK




Fig. 5 TO-247-3

