

**ADVANCED
POWER
TECHNOLOGY®**

| | | |
|------------------|-------------|------------|
| APT30S20B | 200V | 45A |
| APT30S20S | 200V | 45A |

HIGH VOLTAGE SCHOTTKY DIODE

| PRODUCT APPLICATIONS | PRODUCT FEATURES | PRODUCT BENEFITS |
|---|---|---|
| <ul style="list-style-type: none"> • Parallel Diode <ul style="list-style-type: none"> -Switchmode Power Supply -Inverters • Free Wheeling Diode <ul style="list-style-type: none"> -Motor Controllers -Converters • Snubber Diode • Uninterruptible Power Supply (UPS) • 48 Volt Output Rectifiers • High Speed Rectifiers | <ul style="list-style-type: none"> • Ultrafast Recovery Times • Soft Recovery Characteristics • Popular TO-247 Package or Surface Mount D³PAK Package • Low Forward Voltage • High Blocking Voltage • Low Leakage Current | <ul style="list-style-type: none"> • Low Losses • Low Noise Switching • Cooler Operation • Higher Reliability Systems • Increased System Power Density |

MAXIMUM RATINGS

All Ratings: $T_C = 25^\circ\text{C}$ unless otherwise specified.

| Symbol | Characteristic / Test Conditions | APT30S20B_S | UNIT |
|-------------------|---|-------------|------------------|
| V_R | Maximum D.C. Reverse Voltage | 200 | Volts |
| V_{RRM} | Maximum Peak Repetitive Reverse Voltage | | |
| V_{RWM} | Maximum Working Peak Reverse Voltage | | |
| $I_F(\text{AV})$ | Maximum Average Forward Current ($T_C = 125^\circ\text{C}$, Duty Cycle = 0.5) | 45 | Amps |
| $I_F(\text{RMS})$ | RMS Forward Current (Square wave, 50% duty) | 121 | |
| I_{FSM} | Non-Repetitive Forward Surge Current ($T_J = 45^\circ\text{C}$, 8.3ms) | 320 | |
| T_J, T_{STG} | Operating and Storage Temperature Range | -55 to 150 | $^\circ\text{C}$ |
| T_L | Lead Temperature Case for 10 Sec. | 300 | |
| E_{VAL} | Avalanche Energy (2A, 15mH) | 30 | mJ |

STATIC ELECTRICAL CHARACTERISTICS

| Symbol | | | MIN | TYP | MAX | UNIT |
|----------|---|--|-----|-----|-----|-------|
| V_F | Forward Voltage | $I_F = 30\text{A}$ | | .80 | .85 | Volts |
| | | $I_F = 60\text{A}$ | | .91 | | |
| | | $I_F = 30\text{A}, T_J = 125^\circ\text{C}$ | | .67 | | |
| I_{RM} | Maximum Reverse Leakage Current | $V_R = V_R \text{ Rated}$ | | | 0.5 | mA |
| | | $V_R = V_R \text{ Rated}, T_J = 125^\circ\text{C}$ | | | 15 | |
| C_T | Junction Capacitance, $V_R = 200\text{V}$ | | 149 | | | pF |

DYNAMIC CHARACTERISTICS

APT30S20B_S

| Symbol | Characteristic | Test Conditions | MIN | TYP | MAX | UNIT |
|-----------|----------------------------------|---|-----|-----|-----|------|
| t_{rr} | Reverse Recovery Time | $I_F = 30A, \frac{di_F}{dt} = -200A/\mu s$ $V_R = 133V, T_C = 25^\circ C$ | - | 55 | | ns |
| Q_{rr} | Reverse Recovery Charge | | - | 188 | | nC |
| I_{RRM} | Maximum Reverse Recovery Current | | - | 6 | - | Amps |
| t_{rr} | Reverse Recovery Time | $I_F = 30A, \frac{di_F}{dt} = -200A/\mu s$ $V_R = 133V, T_C = 125^\circ C$ | - | 97 | | ns |
| Q_{rr} | Reverse Recovery Charge | | - | 448 | | nC |
| I_{RRM} | Maximum Reverse Recovery Current | | - | 9 | - | Amps |
| t_{rr} | Reverse Recovery Charge | $I_F = 30A, \frac{di_F}{dt} = -700A/\mu s$ $V_R = 133V, T_C = 125^\circ C$ | - | 66 | | ns |
| Q_{rr} | Reverse Recovery Charge | | - | 963 | | nC |
| I_{RRM} | Maximum Reverse Recovery Current | | - | 24 | | Amps |

THERMAL AND MECHANICAL CHARACTERISTICS

| Symbol | Characteristic / Test Conditions | MIN | TYP | MAX | UNIT |
|-----------------|--|-----|------|-----|-------|
| $R_{\theta JC}$ | Junction-to-Case Thermal Resistance | | | .58 | °C/W |
| $R_{\theta JA}$ | Junction-to-Ambient Thermal Resistance | | | 40 | |
| W_T | Package Weight | | 0.22 | | oz |
| | | | 5.9 | | g |
| Torque | Maximum Mounting Torque | | | 10 | lb•in |
| | | | | 1.1 | N•m |

APT Reserves the right to change, without notice, the specifications and information contained herein.




FIGURE 1a. MAXIMUM EFFECTIVE TRANSIENT THERMAL IMPEDANCE, JUNCTION-TO-CASE vs. PULSE DURATION




FIGURE 1b, TRANSIENT THERMAL IMPEDANCE MODEL

TYPICAL PERFORMANCE CURVES




Figure 2. Forward Current vs. Forward Voltage




Figure 4. Reverse Recovery Charge vs. Current Rate of Change




Figure 6. Dynamic Parameters vs. Junction Temperature




Figure 8. Junction Capacitance vs. Reverse Voltage

APT30S20B_S




Figure 3. Reverse Recovery Time vs. Current Rate of Change




Figure 5. Reverse Recovery Current vs. Current Rate of Change




Figure 7. Maximum Average Forward Current vs. Case Temperature




Figure 9. Diode Test Circuit

- ① I_F - Forward Conduction Current
- ② di_F/dt - Rate of Diode Current Change Through Zero Crossing.
- ③ I_{RRM} - Maximum Reverse Recovery Current.
- ④ t_{rr} - Reverse Recovery Time, measured from zero crossing where diode current goes from positive to negative, to the point at which the straight line through I_{RRM} and $0.25 \cdot I_{RRM}$ passes through zero.
- ⑤ Q_{rr} - Area Under the Curve Defined by I_{RRM} and t_{rr} .






Figure 10. Diode Reverse Recovery Waveform and Definitions

TO-247 Package Outline



Dimensions in Millimeters and (Inches)

D³PAK Package Outline

Dimensions in Millimeters (Inches)