

UL Online Certifications Directory

OBOR2.E51047 Varnishes - Component

Page Bottom

Varnishes - Component

[See General Information for Varnishes - Component](#)

JOHN C DOLPH CO

E51047

320 NEW RD

PO BOX 267


MONMOUTH JUNCTION, NJ 08852 USA

Varnish Dsg	ANSI Magnet Wire Type	Varnish Thermal Class C		
		TP	HC	CE
AC-43, EB-43-HG	MW28	130	130	—
EB-43-FB,	MW24	155	155	—
AC-43-66	MW35	180	180	—
BC-325	MW35	200	200	—
BC-340	MW24	155	180	—
	MW35	180	200	—
BC-346A, -346B,	MW16	240	200	—
-346AN, -346-E, BB-348,	MW24	155	180	—
BB-353, -346-HF, BC-346HF, BC-370,	MW28	155	130	—
BG-346A	MW30	180	180	—
	MW35	200	200	180
	MW76	180	180	—
BC-352	MW35	180	—	—
	MW16	220	—	—
BC-354	MW28	130	130	—
BC-356,	MW24	155	155	—
BC-359, PDR-1695,	MW28	130	130	—
-359MS	MW35	180	200	—
	MW16	220	—	—
	MW76	180	180	—
BC-362	MW35	180	200	—
	MW16	220	180	—
CC-1080L, -1082,	MW28	130	130	—
-1094,-1096,	MW16	220	—	—
CC-1250, -1260, -1260LV, -1260T,	MW35	180	200	

				—
CN-1139	MW76	180	180	—
CC-1105, CC-1105-BC, -1105HTC, CC-1103,	MW28	130	130	—
-1105OPT, -1105OPT/HTC, CC-1105LV,	MW16	220	180	—
CB-1105HTC, PDR-1933,	MW35	200	200	—
PDR-1815, -1711,				
CC-1155, CC-1156, PDR-1930, CC-1106				
CC-1141,	MW16	220	180	—
CC-1144,-1144LV	MW35	200	200	—
CC-1122	MW24	155	—	—
	MW76	180	—	—
PDR-991	MW28	130	130	—
	MW35	180	200	—
PDR-1177	MW35	180	180	—
PDR-1334,	MW28	130	130	—
-1334Y	MW24	155	155	—
	MW35	180	200	—
	MW76	180	180	—
PDR-1625	MW35	180	—	—
PDR-1790, PDR-1834	MW28	130	130	—
	MW76	180	180	—
	MW35	180	200	—
PDR-1840,-1874, PDR-1839,	MW76	180	180	—
BC-363	MW35	180	200	—
	MW16	200	—	—
	MW28	130	—	—
SLD-1205,	MW35	180	200	—
CC-1405,	MW16	220	—	—
CB-1405,	MW28	130	—	—
PDR-1931	MW76	180	180	—
CC-1133TR	MW16	240	130	—
CC-1133,	MW76	180	200	—
CC-1157	MW16	220	—	—
	MW28	130	—	—
CC-1305,,	MW16	220	155	—
CC-1305-HTC,	MW28	130	—	—
CC-1305/503D	MW76	180	180	—
CC-1305-HTC-FC				

PDR-1936,	MW16	220	200	—
BC-365,	MW35	180	200	—
BC-365-LTC,	MW76	180	180	—
BC-365-LO	MW80	155	155	—
EX-74100,	MW16	220	—	—
CC-1251,	MW35	180	180	—
-1261	MW80	155	155	—
EX-60076,	MW35	180	180	—
CC-1143				
CC-1149, -1149FC , CC-1149HTC, CC-1149HTC-FC,	MW16	220	155	—
CB-1149,	MW28	130	—	—
CC-1158, CB-1159	MW35	180	—	—
CC-1118-ED,	MW16	200	—	—
PDR-1949, CC-1152				
CC-1118-LV	MW16	200	155	—
	MW28	130	—	—
AC-41,	MW28C	130	—	—
AC-46				
CC-1099	MW16	220	—	—
	MW28C	105	—	—
	MW35C	180	—	—
CC-1126	MW28C	130	—	—
XL-2101, -2103LV	MW16	220	—	—
XL-2101T,	MW28	130	—	—
XL-2109, XL-2101OPT,	MW35	180	—	—
XL-2102, XL-2102OPT, XL-2103,				
XL-2104, XL-2105,				
XL-2106,				
XL-2107, XL-2108				
EX-88077	MW35	180	—	—
CC-1115	MW16	200	—	—
	MW28	130	—	—
	MW35	180	—	—
XL-2110	MW35	200	—	—



Marking: Company name or trademark "SYNTHITE" , "HI-THERM", "DOLPHON" or ) and varnish designation on shipping container.

Last Updated on 2006-06-09

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Listed and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Designs and/or Listings (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from Underwriters Laboratories Inc." must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "Copyright © 2006 Underwriters Laboratories Inc.®"

An independent organization working for a safer world with integrity, precision and knowledge.

