

怡冠电子（深圳）有限公司

地址：深圳市宝安区龙华镇民治宝山工业区

电话：0755-21912166 29806577 13510918098



传真：0755-29806577

E-mail: everyquar@163.com

U F 型磁芯：编码顺序：**R12K**—**UF10.5**—**(M)**
(材质) (规格) (镜面抛光)

U F CORES: Ordering Code: Material Core Size Mirror Lapping

图形：
Shape



型号 Type	尺寸Dimensions (mm)					
	A	B	C	D	E	F
UF8.6	8.6 ± 0.2	6.45 ± 0.2	3.6 ± 0.2	4.0 min	2.2 ± 0.15	4.2 ± 0.2
UF9.8	9.8 ± 0.3	7.1 ± 0.2	2.9 ± 0.2	4.1 min	2.9 ± 0.2	4.3 ± 0.2
UF10.1	10.1 ± 0.3	7.5 ± 0.25	2.9 ± 0.2	3.9 min	2.95 ± 0.15	4.5 ± 0.25
UF10.5	10.5 ± 0.3	7.8 ± 0.2	5.0 ± 0.3	5.2 min	2.4 ± 0.2	5.3 ± 0.3
UF15.7	15.7 ± 0.3	9.7 ± 0.5	6.0 ± 0.3	6.3 min	4.5 ± 0.2	6.0 ± 0.3
UF16	16.0 ± 0.4	10.0 ± 0.3	6.0 ± 0.2	6.7 min	4.6 ± 0.2	6.0 ± 0.3
UF20	19.7 ± 0.4	17.7 ± 0.2	6.0 ± 0.2	7.4 min	6.0 ± 0.2	11.7 ± 0.2
UF30	30.6 ± 0.6	12.1 ± 0.2	6.2 ± 0.2	17.0 min	6.2 ± 0.3	6.1 ± 0.3

型号 Type	电感因数 A_L (nH/N ²) ± 25%				重量 (克/付) W (g/pair)
	R7k	R10k	R12k	R15k	
UF8.6	960	1600	1900	2100	1.3
UF9.8	1200	1600	1800	2000	1.5
UF10.1	1400	1900	2400	3100	1.6
UF10.5	1600	2400	3100	4100	2.5
UF15.7	2600	3200	3600	4200	6.1
UF16	2800	3600	4500	5500	6.9
UF20	2750	3800	4500	5400	14.3
UF30	4300	6100	7300	9100	14.6

注： A_L 值测试条件：1KHz, 250mV, 100Ts, 25℃。

以上为本公司标准规格，可根据客户特殊要求进行设计。

Remark: Testing condition for A_L : 1KHz, 250mV, 100Ts, 25℃.

The above is the usually type, we can redesign according to customer's request.