



Site: Phase: *L1* Temperature: 26  
 Limit: EN55022 Class B Conduction(QP) Power: AC 230V/50Hz Humidity: 60 %  
 EUT: ADAPTOR  
 M/N: 5V1A  
 Mode: NORMAL  
 Note:

No.	Freq. MHz	Reading_Level (dBuV)			Correct Factor dB	Measurement (dBuV)			Limit (dBuV)		Margin (dB)		P/F	Comment
		Peak	QP	AVG		peak	QP	AVG	QP	AVG	QP	AVG		
1	0.3250	55.59		43.86	0.03	55.62		43.89	59.58	49.58	-3.96	-5.69	P	
2	0.4335	52.50		34.53	0.03	52.53		34.56	57.19	47.19	-4.66	-12.63	P	
3	0.7550	56.08		45.62	0.02	56.10		45.64	56.00	46.00	0.10	-0.36	F	
4	1.9400	59.38	54.72	39.86	0.02	59.40	54.74	39.88	56.00	46.00	-1.26	-6.12	P	
5	2.8775	59.02		39.70	0.03	59.05		39.73	56.00	46.00	3.05	-6.27	F	
6	22.5000	36.89		19.41	0.19	37.08		19.60	60.00	50.00	-22.92	-30.40	P	
7	4.0550	52.79		37.45	0.03	52.82		37.48	56.00	46.00	-3.18	-8.52	P	