

EI 12

| 变压器温升 ΔT | 线路结构 F/B | 工作频率 KHz | 输出功率 Pout(W) | 最大磁通 Bm(Mt) | 工作磁通 ΔB (mT) | 每匝电阻 (μ Ω /T) | 每匝电压 (V/T) | 磁芯损耗 PFE(W) | 占空比 D | 窗口使用面积 Acw*Ko(m ²) |
|----------|----------|----------|--------------|-------------|--------------|----------------|------------|-------------|-------|--------------------------------|
| 10° C | F | 50 | 2.6 | 228.0 | 195.9 | 296 | 0.379 | 0.096 | 0.3 | 2.249 |
| | | 100 | 5.3 | 228 | 195.9 | 296 | 0.757 | 0.096 | 0.3 | 2.249 |
| | B | 50 | 6.8 | 228 | 195.9 | 358 | 0.757 | 0.096 | 0.6 | 1.863 |
| | | 100 | 12.69 | 182.7 | 182.7 | 358 | 1.413 | 0.096 | 0.6 | 1.863 |
| 20° C | F | 50 | 3.7 | 228 | 195.9 | 296 | 0.379 | 0.192 | 0.3 | 2.249 |
| | | 100 | 7.47 | 228 | 195.9 | 296 | 0.757 | 0.192 | 0.3 | 2.249 |
| | B | 50 | 9.6 | 228 | 195.9 | 358 | 0.757 | 0.192 | 0.6 | 1.863 |
| | | 100 | 19.2 | 228 | 195.9 | 358 | 1.515 | 0.192 | 0.6 | 1.863 |
| 30° C | F | 50 | 4.6 | 228 | 195.9 | 296 | 0.379 | 0.283 | 0.3 | 2.249 |
| | | 100 | 9.1 | 228 | 195.9 | 296 | 0.757 | 0.288 | 0.3 | 2.249 |
| | B | 50 | 11.8 | 228 | 195.9 | 358 | 0.757 | 0.288 | 0.6 | 1.863 |
| | | 100 | 23.5 | 228 | 195.9 | 358 | 1.515 | 0.288 | 0.6 | 1.863 |
| 40° C | F | 50 | 5.3 | 288 | 195.9 | 296 | 0.379 | 0.385 | 0.3 | 2.249 |
| | | 100 | 10.5 | 228 | 195.9 | 296 | 0.757 | 0.385 | 0.3 | 2.249 |
| | B | 50 | 13.6 | 288 | 195.9 | 358 | 0.757 | 0.385 | 0.6 | 1.863 |
| | | 100 | 27.2 | 228 | 195.9 | 358 | 1.515 | 0.385 | 0.6 | 1.863 |

EI 16

| 变压器温升 ΔT | 线路结构 F/B | 工作频率 KHz | 输出功率 Pout(W) | 最大磁通 Bm(Mt) | 工作磁通 ΔB (mT) | 每匝电阻 (μ Ω /T) | 每匝电压 (V/T) | 磁芯损耗 PFE(W) | 占空比 D | 窗口使用面积 Acw*Ko(m ²) |
|----------|----------|----------|--------------|-------------|--------------|----------------|------------|-------------|-------|--------------------------------|
| 10° C | F | 50 | 8.2 | 228 | 195.9 | 98.77 | 0.627 | 0.112 | 0.3 | 8.06 |
| | | 100 | 15.2 | 211 | 182.4 | 98.77 | 1.167 | 0.112 | 0.3 | 8.06 |
| | B | 50 | 24.9 | 194.2 | 194.2 | 119.22 | 1.242 | 0.112 | 0.6 | 6.68 |
| | | 100 | 27.9 | 129.7 | 129.7 | 119.22 | 1.660 | 0.112 | 0.6 | 6.68 |
| 20° C | F | 50 | 11.6 | 228 | 195.9 | 98.77 | 0.627 | 0.225 | 0.3 | 8.06 |
| | | 100 | 23.2 | 228 | 195.9 | 98.77 | 1.253 | 0.225 | 0.3 | 8.06 |
| | B | 50 | 29.8 | 228 | 195.9 | 119.22 | 1.254 | 0.225 | 0.6 | 6.68 |
| | | 100 | 53.3 | 175.9 | 175.9 | 119.22 | 2.252 | 0.225 | 0.6 | 6.68 |
| 30° C | F | 50 | 14 | 228 | 195.9 | 98.77 | 0.627 | 0.337 | 0.3 | 8.06 |
| | | 100 | 28 | 228 | 195.9 | 98.77 | 1.254 | 0.337 | 0.3 | 8.06 |
| | B | 50 | 36 | 228 | 195.9 | 119.22 | 1.254 | 0.337 | 0.6 | 6.68 |
| | | 100 | 78 | 210.1 | 210.1 | 119.22 | 2.689 | 0.337 | 0.6 | 6.68 |
| 40° C | F | 50 | 16 | 228 | 195.9 | 98.77 | 0.627 | 0.449 | 0.3 | 8.06 |
| | | 100 | 33 | 228 | 195.9 | 98.77 | 1.254 | 0.449 | 0.3 | 8.06 |
| | B | 50 | 42 | 228 | 195.9 | 119.22 | 1.254 | 0.449 | 0.6 | 6.68 |
| | | 100 | 84 | 228 | 195.9 | 119.22 | 2.507 | 0.449 | 0.6 | 6.68 |

EI 19

| 变压器温升 ΔT | 线路结构 F/B | 工作频率 KHz | 输出功率 Pout(W) | 最大磁通 Bm(Mt) | 工作磁通 ΔB (mT) | 每匝电阻 (μ Ω /T) | 每匝电压 (V/T) | 磁芯损耗 PFE(W) | 占空比 D | 窗口使用面积 Acw*Ko(m ²) |
|----------|----------|----------|--------------|-------------|--------------|----------------|------------|-------------|-------|--------------------------------|
| 10° C | F | 50 | 12 | 228 | 195.9 | 81.2 | 0.744 | 0.132 | 0.3 | 11.1 |
| | | 100 | 20 | 197.5 | 171.5 | 81.2 | 1.303 | 0.132 | 0.3 | 11.1 |
| | B | 50 | 27 | 175.8 | 175.8 | 98.02 | 1.336 | 0.132 | 0.6 | 9.195 |
| | | 100 | 37 | 121.6 | 121.6 | 98.02 | 1.848 | 0.132 | 0.6 | 9.195 |
| 20° C | F | 50 | 16 | 228 | 195.9 | 81.2 | 0.744 | 0.263 | 0.3 | 11.1 |
| | | 100 | 33 | 228 | 195.9 | 81.2 | 1.489 | 0.263 | 0.3 | 11.1 |
| | B | 50 | 42 | 228 | 195.9 | 98.02 | 1.489 | 0.263 | 0.6 | 9.195 |
| | | 100 | 71 | 164.7 | 164.7 | 98.02 | 2.503 | 0.263 | 0.6 | 9.195 |
| 30° C | F | 50 | 20 | 228 | 195.9 | 81.2 | 0.744 | 0.395 | 0.3 | 11.1 |
| | | 100 | 40 | 228 | 195.9 | 81.2 | 1.489 | 0.395 | 0.3 | 11.1 |
| | B | 50 | 52 | 228 | 195.9 | 98.02 | 1.489 | 0.395 | 0.6 | 9.195 |
| | | 100 | 104 | 196.7 | 196.7 | 98.02 | 2.99 | 0.395 | 0.6 | 9.195 |
| 40° C | F | 50 | 23 | 228 | 195.9 | 81.2 | 0.744 | 0.526 | 0.3 | 11.1 |
| | | 100 | 46 | 228 | 195.9 | 81.2 | 1.484 | 0.526 | 0.3 | 11.1 |
| | B | 50 | 60 | 228 | 195.9 | 98.02 | 1.484 | 0.526 | 0.6 | 9.195 |
| | | 100 | 136 | 223 | 223 | 98.02 | 3.390 | 0.526 | 0.6 | 9.195 |

EI 25

| 变压器温升 ΔT | 线路结构 F/B | 工作频率 KHz | 输出功率 Pout(W) | 最大磁通 Bm(Mt) | 工作磁通 ΔB (mT) | 每匝电阻 (μ Ω /T) | 每匝电压 (V/T) | 磁芯损耗 PFE(W) | 占空比 D | 窗口使用面积 Acw*Ko(m ²) |
|----------|----------|----------|--------------|-------------|--------------|----------------|------------|-------------|-------|--------------------------------|
| 10° C | F | 50 | 22 | 211.1 | 182.4 | 87.08 | 1.335 | 0.156 | 0.3 | 13.896 |
| | | 100 | 33 | 155.2 | 137.4 | 87.08 | 2.011 | 0.156 | 0.3 | 13.896 |
| | B | 50 | 43 | 139.3 | 139.3 | 105.1 | 2.038 | 0.156 | 0.6 | 11.512 |
| | | 100 | 59 | 96.1 | 96.1 | 105.1 | 2.813 | 0.156 | 0.6 | 11.512 |
| 20° C | F | 50 | 33 | 228 | 195.9 | 87.08 | 1.433 | 0.313 | 0.3 | 13.896 |
| | | 100 | 61 | 209.3 | 181 | 87.08 | 2.649 | 0.313 | 0.3 | 13.896 |
| | B | 50 | 81 | 184.7 | 184.7 | 105.1 | 2.703 | 0.313 | 0.6 | 11.512 |
| | | 100 | 113 | 129.7 | 129.7 | 105.1 | 3.796 | 0.313 | 0.6 | 11.512 |
| 30° C | F | 50 | 41 | 228 | 195.9 | 87.08 | 1.433 | 0.469 | 0.3 | 13.896 |
| | | 100 | 81 | 228 | 195.9 | 87.08 | 2.867 | 0.469 | 0.3 | 13.896 |
| | B | 50 | 117 | 217.8 | 217.8 | 105.1 | 3.184 | 0.469 | 0.6 | 11.512 |
| | | 100 | 165 | 154.5 | 154.5 | 105.1 | 4.522 | 0.469 | 0.6 | 11.512 |
| 40° C | F | 50 | 47 | 228 | 195.9 | 87.08 | 1.433 | 0.625 | 0.3 | 13.896 |
| | | 100 | 94 | 228 | 195.9 | 87.08 | 2.867 | 0.625 | 0.3 | 13.896 |
| | B | 50 | 121 | 228 | 195.9 | 105.1 | 2.867 | 0.625 | 0.6 | 11.512 |
| | | 100 | 216 | 174.9 | 174.9 | 105.1 | 5.119 | 0.625 | 0.6 | 11.512 |

EI 28

| 变压器温升 ΔT | 线路结构 F/B | 工作频率 KHz | 输出功率 Pout(W) | 最大磁通 Bm(Mt) | 工作磁通 ΔB (mT) | 每匝电阻 ($\mu\Omega$ / /T) | 每匝电压 (V/T) | 磁芯损耗 PFE(W) | 占空比 D | 窗口使用面积 Acw*Ko(m ²) |
|------------------|----------|-------------|-----------------|----------------|-------------------------|--------------------------------|---------------|----------------|----------|-----------------------------------|
| 10° C | F | 50 | 25 | 150.2 | 133.5 | 103.7 | 1.713 | 0.128 | 0.3 | 13.96 |
| | | 100 | 34 | 106.5 | 98.2 | 103.7 | 2.520 | 0.128 | 0.3 | 13.96 |
| | B | 50 | 44 | 97.5 | 97.5 | 125.2 | 2.502 | 0.128 | 0.6 | 11.57 |
| | | 100 | 60 | 66.3 | 66.3 | 125.2 | 3.003 | 0.128 | 0.6 | 11.57 |
| 20° C | F | 50 | 43 | 210.4 | 174.7 | 103.7 | 2.242 | 0.256 | 0.3 | 13.96 |
| | | 100 | 63 | 143.1 | 127.8 | 103.7 | 3.280 | 0.256 | 0.3 | 13.96 |
| | B | 50 | 83 | 130.7 | 130.7 | 125.2 | 3.355 | 0.256 | 0.6 | 11.57 |
| | | 100 | 113 | 89.2 | 89.2 | 125.2 | 4.579 | 0.256 | 0.6 | 11.57 |
| 30° C | F | 50 | 50 | 228 | 195.9 | 103.7 | 2.514 | 0.384 | 0.3 | 13.96 |
| | | 100 | 91 | 170.2 | 169.5 | 103.7 | 3.837 | 0.384 | 0.3 | 13.96 |
| | B | 50 | 121 | 155.2 | 155.2 | 125.2 | 3.983 | 0.384 | 0.6 | 11.57 |
| | | 100 | 165 | 160.0 | 106.0 | 125.2 | 5.441 | 0.384 | 0.6 | 11.57 |
| 40° C | F | 50 | 68 | 228 | 195.9 | 103.7 | 2.514 | 0.513 | 0.3 | 13.96 |
| | | 100 | 117 | 192.4 | 167.4 | 103.7 | 4.297 | 0.513 | 0.3 | 13.96 |
| | B | 50 | 158 | 175.3 | 175.3 | 125.2 | 4.499 | 0.513 | 0.6 | 11.57 |
| | | 100 | 216 | 119.9 | 119.9 | 125.2 | 6.155 | 0.513 | 0.6 | 11.57 |

EI 30

| 变压器温升 ΔT | 线路结构 F/B | 工作频率 KHz | 输出功率 Pout(W) | 最大磁通 Bm(Mt) | 工作磁通 ΔB (mT) | 每匝电阻 ($\mu\Omega$ / /T) | 每匝电压 (V/T) | 磁芯损耗 PFE(W) | 占空比 D | 窗口使用面积 Acw*Ko(m ²) |
|------------------|----------|-------------|-----------------|----------------|-------------------------|--------------------------------|---------------|----------------|----------|-----------------------------------|
| 10° C | F | 50 | 50 | 163.6 | 144.2 | 104.0 | 2.740 | 0.227 | 0.3 | 14.364 |
| | | 100 | 72 | 114.2 | 104.4 | 104.0 | 3.967 | 0.227 | 0.3 | 14.364 |
| | B | 50 | 98 | 110.5 | 110.5 | 125.6 | 4.199 | 0.227 | 0.6 | 11.90 |
| | | 100 | 128 | 72.0 | 72.0 | 125.6 | 5.472 | 0.227 | 0.6 | 11.90 |
| 20° C | F | 50 | 90 | 213.5 | 184.4 | 104.0 | 3.504 | 0.454 | 0.3 | 14.364 |
| | | 100 | 131 | 152.3 | 135.1 | 104.0 | 5.134 | 0.454 | 0.3 | 14.364 |
| | B | 50 | 181 | 144.2 | 144.2 | 125.6 | 5.480 | 0.454 | 0.6 | 11.90 |
| | | 100 | 214 | 96.1 | 96.1 | 125.6 | 7.304 | 0.454 | 0.6 | 11.90 |
| 30° C | F | 50 | 117 | 228 | 195.9 | 104.0 | 3.72 | 0.682 | 0.3 | 14.364 |
| | | 100 | 188 | 180.3 | 157.7 | 104.0 | 5.993 | 0.682 | 0.3 | 14.364 |
| | B | 50 | 258 | 168.5 | 168.5 | 125.6 | 6.403 | 0.682 | 0.6 | 11.90 |
| | | 100 | 349 | 113.7 | 113.7 | 125.6 | 8.641 | 0.682 | 0.6 | 11.90 |
| 40° C | F | 50 | 135 | 228 | 195.9 | 104.0 | 3.722 | 0.909 | 0.3 | 14.364 |
| | | 100 | 242 | 203.2 | 176.1 | 104.0 | 6.692 | 0.909 | 0.3 | 14.364 |
| | B | 50 | 333 | 188.2 | 188.2 | 125.6 | 7.152 | 0.909 | 0.6 | 11.90 |
| | | 100 | 454 | 128.2 | 128.2 | 125.6 | 9.473 | 0.909 | 0.6 | 11.90 |

EI 33

| 变压器温升 ΔT | 线路结构 F/B | 工作频率 KHz | 输出功率 Pout(W) | 最大磁通 Bm(Mt) | 工作磁通 ΔB (mT) | 每匝电阻 (μ Ω /T) | 每匝电压 (V/T) | 磁芯损耗 PFE(W) | 占空比 D | 窗口使用面积 Acw*Ko(m ²) |
|----------|----------|----------|--------------|-------------|--------------|----------------|------------|-------------|-------|--------------------------------|
| 10° C | F | 50 | 63 | 151.1 | 134.1 | 79.86 | 2.754 | 0.287 | 0.3 | 22.176 |
| | | 100 | 94 | 109.4 | 100.6 | 79.86 | 4.131 | 0.287 | 0.3 | 22.176 |
| | B | 50 | 119 | 98.2 | 98.2 | 96.4 | 4.033 | 0.287 | 0.6 | 18.371 |
| | | 100 | 165 | 68.4 | 68.4 | 96.4 | 5.618 | 0.287 | 0.6 | 18.371 |
| 20° C | F | 50 | 116 | 202 | 175.4 | 79.86 | 3.602 | 0.556 | 0.3 | 22.176 |
| | | 100 | 173 | 146.7 | 130.6 | 79.86 | 5.363 | 0.556 | 0.3 | 22.176 |
| | B | 50 | 225 | 131.5 | 131.5 | 96.4 | 5.400 | 0.556 | 0.6 | 18.371 |
| | | 100 | 314 | 91.8 | 91.8 | 96.4 | 7.540 | 0.556 | 0.6 | 18.371 |
| 30° C | F | 50 | 159 | 228 | 195.9 | 79.86 | 4.022 | 0.833 | 0.3 | 22.176 |
| | | 100 | 248 | 174.2 | 152.7 | 79.86 | 6.271 | 0.833 | 0.3 | 22.176 |
| | B | 50 | 326 | 156 | 156 | 96.4 | 6.406 | 0.833 | 0.6 | 18.371 |
| | | 100 | 455 | 108.9 | 108.9 | 96.4 | 8.944 | 0.833 | 0.6 | 18.371 |
| 40° C | F | 50 | 184 | 228 | 195.9 | 79.86 | 4.022 | 1.111 | 0.3 | 22.176 |
| | | 100 | 320 | 196.7 | 170.9 | 79.86 | 7.018 | 1.111 | 0.3 | 22.176 |
| | B | 50 | 425 | 176.2 | 176.2 | 96.4 | 7.236 | 1.111 | 0.6 | 18.371 |
| | | 100 | 594 | 123.0 | 123.0 | 96.4 | 10.102 | 1.111 | 0.6 | 18.371 |

EI 35

| 变压器温升 ΔT | 线路结构 F/B | 工作频率 KHz | 输出功率 Pout(W) | 最大磁通 Bm(Mt) | 工作磁通 ΔB (mT) | 每匝电阻 (μ Ω /T) | 每匝电压 (V/T) | 磁芯损耗 PFE(W) | 占空比 D | 窗口使用面积 Acw*Ko(m ²) |
|----------|----------|----------|--------------|-------------|--------------|----------------|------------|-------------|-------|--------------------------------|
| 10° C | F | 50 | 68 | 170.5 | 149.7 | 60.71 | 2.495 | 0.303 | 0.3 | 27.636 |
| | | 100 | 98 | 117.3 | 107 | 60.71 | 3.566 | 0.303 | 0.3 | 27.636 |
| | B | 50 | 128 | 108.8 | 108.8 | 73.29 | 3.627 | 0.303 | 0.6 | 22.894 |
| | | 100 | 170 | 72.4 | 72.4 | 73.29 | 4.827 | 0.303 | 0.6 | 22.894 |
| 20° C | F | 50 | 126 | 228 | 195.9 | 60.71 | 3.265 | 0.606 | 0.3 | 27.636 |
| | | 100 | 180 | 158.6 | 140.2 | 60.71 | 4.673 | 0.606 | 0.3 | 27.636 |
| | B | 50 | 245 | 147.5 | 147.5 | 73.29 | 4.917 | 0.606 | 0.6 | 22.894 |
| | | 100 | 325 | 97.9 | 97.9 | 73.29 | 6.927 | 0.606 | 0.6 | 22.894 |
| 30° C | F | 50 | 155 | 228 | 195.9 | 60.71 | 3.265 | 0.909 | 0.3 | 27.636 |
| | | 100 | 260 | 189.2 | 164.8 | 60.71 | 5.493 | 0.909 | 0.3 | 27.636 |
| | B | 50 | 358 | 176.3 | 176.3 | 73.29 | 5.877 | 0.909 | 0.6 | 22.894 |
| | | 100 | 475 | 116.8 | 116.8 | 73.29 | 7.787 | 0.909 | 0.6 | 22.894 |
| 40° C | F | 50 | 179 | 228 | 195.9 | 60.71 | 3.265 | 1.212 | 0.3 | 27.636 |
| | | 100 | 338 | 214.4 | 185.1 | 60.71 | 6.170 | 1.212 | 0.3 | 27.636 |
| | B | 50 | 470 | 200.1 | 200.1 | 73.29 | 6.67 | 1.212 | 0.6 | 22.894 |
| | | 100 | 622 | 132.4 | 132.4 | 73.29 | 8.27 | 1.212 | 0.6 | 22.894 |

EI 40

| 变压器温升 ΔT | 线路结构 F/B | 工作频率 KHz | 输出功率 Pout(W) | 最大磁通 Bm(Mt) | 工作磁通 ΔB (mT) | 每匝电阻 (μ Ω /T) | 每匝电压 (V/T) | 磁芯损耗 PFE(W) | 占空比 D | 窗口使用面积 Acw*Ko(m ²) |
|----------|----------|----------|--------------|-------------|--------------|----------------|------------|-------------|-------|--------------------------------|
| 10° C | F | 50 | 95 | 151.2 | 134.3 | 5.272 | 3.021 | 0.345 | 0.3 | 35.31 |
| | | 100 | 138 | 106.2 | 98 | 5.272 | 4.41 | 0.345 | 0.3 | 35.31 |
| | B | 50 | 189 | 103.9 | 103.9 | 63.64 | 4.676 | 0.345 | 0.6 | 29.252 |
| | | 100 | 246 | 67.8 | 67.8 | 63.64 | 6.102 | 0.345 | 0.6 | 29.252 |
| 20° C | F | 50 | 169 | 195 | 169.5 | 5.272 | 3.814 | 0.690 | 0.3 | 35.31 |
| | | 100 | 250 | 140.5 | 125.6 | 5.272 | 5.652 | 0.690 | 0.3 | 35.31 |
| | B | 50 | 344 | 134 | 134 | 63.64 | 6.03 | 0.690 | 0.6 | 29.252 |
| | | 100 | 460 | 89.7 | 89.7 | 63.64 | 8.073 | 0.690 | 0.6 | 29.252 |
| 30° C | F | 50 | 238 | 226.3 | 194.7 | 5.272 | 4.381 | 1.034 | 0.3 | 35.31 |
| | | 100 | 356 | 165.6 | 145.8 | 5.272 | 6.561 | 1.034 | 0.3 | 35.31 |
| | B | 50 | 489 | 155.6 | 155.6 | 63.64 | 7.002 | 1.034 | 0.6 | 29.252 |
| | | 100 | 664 | 105.7 | 105.7 | 63.64 | 9.513 | 1.034 | 0.6 | 29.252 |
| 40° C | F | 50 | 276 | 228 | 195.9 | 5.272 | 4.408 | 1.379 | | 35.31 |
| | | 100 | 457 | 186 | 162.2 | 5.272 | 7.299 | 1.379 | 0.3 | 35.31 |
| | B | 50 | 627 | 172.9 | 172.9 | 63.64 | 7.781 | 1.379 | 0.6 | 29.252 |
| | | 100 | 862 | 118.8 | 118.8 | 63.64 | 10.692 | 1.379 | 0.6 | 29.252 |

EI 50

| 变压器温升 ΔT | 线路结构 F/B | 工作频率 KHz | 输出功率 Pout(W) | 最大磁通 Bm(Mt) | 工作磁通 ΔB (mT) | 每匝电阻 (μ Ω /T) | 每匝电压 (V/T) | 磁芯损耗 PFE(W) | 占空比 D | 窗口使用面积 Acw*Ko(m ²) |
|----------|----------|----------|--------------|-------------|--------------|----------------|------------|-------------|-------|--------------------------------|
| 10° C | F | 50 | 173 | 128.9 | 116.3 | 38.95 | 4.129 | 0.455 | 0.3 | 59.112 |
| | | 100 | 255 | 91.1 | 85.8 | 38.95 | 6.092 | 0.455 | 0.3 | 59.112 |
| | B | 50 | 330 | 86.4 | 86.4 | 47.02 | 6.134 | 0.455 | 0.6 | 48.97 |
| | | 100 | 452 | 59.1 | 59.1 | 47.02 | 8.392 | 0.455 | 0.6 | 48.97 |
| 20° C | F | 50 | 312 | 169 | 148.6 | 38.95 | 5.275 | 0.909 | 0.3 | 59.112 |
| | | 100 | 456 | 119.2 | 108.5 | 38.95 | 7.704 | 0.909 | 0.3 | 59.112 |
| | B | 50 | 613 | 113.3 | 113.3 | 47.02 | 8.044 | 0.909 | 0.6 | 48.97 |
| | | 100 | 838 | 77.5 | 77.5 | 47.02 | 8.044 | 0.909 | 0.6 | 48.97 |
| 30° C | F | 50 | 442 | 198.1 | 172 | 38.95 | 6.106 | 1.364 | 0.3 | 59.112 |
| | | 100 | 643 | 139.6 | 124.9 | 38.95 | 8.868 | 1.364 | 0.3 | 59.112 |
| | B | 50 | 879 | 132.8 | 132.8 | 47.02 | 9.429 | 1.364 | 0.6 | 48.97 |
| | | 100 | 1201 | 90.7 | 90.7 | 47.02 | 12.88 | 1.364 | 0.6 | 48.97 |
| 40° C | F | 50 | 567 | 221.7 | 191 | 38.95 | 6.781 | 1.818 | 0.3 | 59.112 |
| | | 100 | 821 | 156.2 | 138.2 | 38.95 | 9.812 | 1.818 | 0.3 | 59.112 |
| | B | 50 | 1136 | 148.1 | 148.6 | 47.02 | 10.55 | 1.818 | 0.6 | 48.97 |
| | | 100 | 1550 | 101.4 | 101.4 | 47.02 | 14.399 | 1.818 | 0.6 | 48.97 |

EI 60

| 变压器温升 ΔT | 线路结构 F/B | 工作频率 KHz | 输出功率 Pout(W) | 最大磁通 Bm(Mt) | 工作磁通 ΔB (mT) | 每匝电阻 ($\mu \Omega$ /T) | 每匝电压 (V/T) | 磁芯损耗 PFE(W) | 占空比 D | 窗口使用面积 Acw*Ko(m ²) |
|------------------|----------|-------------|-----------------|----------------|-------------------------|----------------------------|---------------|----------------|----------|-----------------------------------|
| 10° C | F | 50 | 218 | 112.6 | 103.1 | 27.51 | 4.176 | 0.5 | 0.3 | 100.6 |
| | | 100 | 322 | 79 | 76.1 | 27.51 | 6.164 | 0.5 | 0.3 | 100.6 |
| | B | 50 | 414 | 76 | 76 | 33.21 | 6.156 | 0.5 | 0.6 | 83.34 |
| | | 100 | 562 | 51.6 | 51.6 | 33.21 | 8.359 | 0.5 | 0.6 | 83.34 |
| 20° C | F | 50 | 391 | 146.9 | 130.8 | 27.51 | 5.297 | 1 | 0.3 | 100.6 |
| | | 100 | 571 | 103 | 95.5 | 27.51 | 7.736 | 1 | 0.3 | 100.6 |
| | B | 50 | 764 | 99.2 | 99.2 | 33.21 | 8.035 | 1 | 0.6 | 83.34 |
| | | 100 | 1036 | 67.3 | 67.3 | 33.21 | 10.90 | 1 | 0.6 | 83.34 |
| 30° C | F | 50 | 552 | 171.6 | 150.7 | 27.51 | 6.103 | 1.5 | 0.3 | 100.6 |
| | | 100 | 801 | 120.3 | 109.4 | 27.51 | 8.861 | 1.5 | 0.3 | 100.6 |
| | B | 50 | 1093 | 115.9 | 115.9 | 33.21 | 9.388 | 1.5 | 0.6 | 83.34 |
| | | 100 | 1484 | 78.7 | 78.7 | 33.21 | 12.57 | 1.5 | 0.6 | 83.34 |
| 40° C | F | 50 | 706 | 191.7 | 166.9 | 27.51 | 6.759 | 2 | 0.3 | 100.6 |
| | | 100 | 1021 | 134.4 | 120.7 | 27.51 | 9.777 | 2 | 0.3 | 100.6 |
| | B | 50 | 1410 | 129.5 | 129.5 | 33.21 | 10.49 | 2 | 0.6 | 83.34 |
| | | 100 | 1912 | 87.8 | 87.8 | 33.21 | 14.22 | 2 | 0.6 | 83.34 |