



Item	Unit	Model		
		PT-EL15WD350C	PT-EL15WD700C	
AC Input voltage	V	220-240	220-240	
AC Input frequency	Hz	50/60	50/60	
Power factor		>0.85	>0.85	
DC Output power	W	15	15	
DC Output voltage	V	48	24	
DC Output current	mA	350	700	
Efficiency		>75%	>75%	
Ambient temperature	°C	40	40	
Max case temperature	°C	80	80	
Thermal protection		YES	YES	
Overload protection		YES	YES	
Overcurrent protection		YES	YES	
Short circuit portection		YES	YES	
Input cables	mm ²	2x0.75	2x0.75	
Output cables section	mm ²	1.5	1.5	
Weight	g			
Dimensiont	mm	103x67x30	103x67x30	
Packging				
N° Max LED 1W W-B-L		12	/	
N° Max LED 1W R-Y		13	/	
N° Max LED 3W W-B-L		/	5	
N° Max LED 3W R-Y		/	6	

1. Dimmable constant current power supply for building in. 2. Hight efficiency and reduced weight and size. 3. Dimmable output current 0-350mA or 0-700mA. 4. Equipped with push-in terminals. 5. Dimmable by means of external 0-10V DC dimmer.

WARNING: LED MODULES SERIAL CONNECTIONS ONLY, NEVER USE SWITCHES ON SECONDARY SIDE.