



Layout Guide:

1. C4靠近IC PIN1
2. Q2 MOS散熱Pad要大, 可以用裸銅或條狀裸銅, 散熱較佳.
3. IC的GND PIN與C4的GND端連接後再接到電源GND, 不可和MOS GND端直接連接.
4. 10W以上功率應用, L1與Q2 MOS不可靠太近, 防止溫度互相烤高.
5. Q2 MOS GND端與C1 GND端連接線儘量粗短.
6. L1/Q2/D1三元件連接端走線儘量粗短.

LED電流設定:
 $I_{LED} = 0.2V/R_p$
 $R_p = R_{10} // R_{11} // R_{12} // R_{13} // R_{14} // R_{15}$, R10--R15電阻併聯

The circuits shown are intended to explain typical application of the products concerned. BITEK is not responsible for any possibly infringement of intellectual property rights owned by any third party that may arise from the use of these circuits. The circuit furnished in this document is the property of BITEK and shall be treated as highly confidentiality; any unauthorized disclosure, copying, distribution, or use is strictly prohibited. The receiver shall fully compensate BITEK without any reservation for any losses thereof due to its violation of BITEK's confidential request. Further, the receiver is deemed to agree on BITEK's confidential request therein otherwise the receiver shall return this document to BITEK immediately.

Beyond Innovation Technology Co., LTD.
 5F, No.136, Sec.3, Nanjing E. Road, Taipei, Taiwan, R.O.C.
 Tel : 886-2-2778-5939 Fax : 886-2-2778-1050

Title BIT3251+B0210D DEMO BOARD			
Size A	Document Number INV-1123-100-242	Task Code <Number>	Rev 1.00
Date: Tuesday, November 08, 2011	Sheet 1	of 1	1