












GPA POWER PRODUCTS LIST 产品目录

PRODUCT PHOTO 产品图片	PRODUCT MODEL 产品型号	PRODUCT SIZE 产品尺寸 (MM)	INPUT AC 输入电压 (V)	OUTPUT POWER 输出功率 (W)	OUTPUT CURRENT 输出电流 (MA)	OUTPUT VOLTAGE 输出电压 (V)	Efficiency 效率	PFC 功率因数	Unit Weight 单重 (G)	QTY/BOX 数量/箱	KG/BOX KG/箱	BOX SIZE 外箱尺寸 (CM)
Waterproof LED Driver-----Constant Voltage for LED Strips, LED Tape 恒压防水电源 主要适用灯条灯带												
	PVA-12008P004	76*38*28	100-240	8	0.67A	12±5%	≥75%	≥0.5	80	92	10.5	38.5*34.5*20
	PVA-24008P004	76*38*29	100-240	8	0.33A	24±5%	≥75%	≥0.5	80	92	10.5	38.5*34.5*20
	PVA-05015M001	160*25*22	100-240	15	3A	5±5%	≥80%	≥0.5	180	50	9.4	37*19.2*16.2
	PVA-12018M001	160*25*22	100-240	18	1.5A	12±5%	≥80%	≥0.5	180	50	9.4	37*19.2*16.2
	PVA-24018M001	160*25*22	100-240	18	0.75A	24±5%	≥80%	≥0.5	180	50	9.4	37*19.2*16.2
	PVA-05015M010	160*33*23	100-240	15	3A	5±5%	≥80%	≥0.5	188	50	10.4	37*19.2*16.2
	PVA-12020M010	160*33*23	100-240	20	1.67A	12±5%	≥80%	≥0.5	188	50	10.4	37*19.2*16.2
	PVA-24020M010	160*33*23	100-240	20	0.84A	24±5%	≥80%	≥0.5	188	50	10.4	37*19.2*16.2
	PVA-12030M013	110*60*28	100-240	30	2.5A	12±5%	≥80%	≥0.5	270	50	13.7	39*22*19
	PVA-24030M013	110*60*28	100-240	30	1.25A	24±5%	≥80%	≥0.5	270	50	13.7	39*22*19
	PVA-12030M002	200*30*20	100-240	30	2.5A	12±5%	≥80%	≥0.5	220	50	11.5	41.5*23.5*15.2
	PVA-24030M002	200*30*20	100-240	30	1.25A	24±5%	≥80%	≥0.5	220	50	11.5	41.5*23.5*15.2
	PVA-36030M002	200*30*20	100-240	30	0.83A	36±5%	≥80%	≥0.5	220	50	11.5	41.5*23.5*15.2
	PVA-05030M003	200*33*23	175-240	30	6A	5±5%	≥75%	≥0.5	280	50	14.9	39*22*19
	PVA-12040M003	200*33*23	100-240	40	3.33A	12±5%	≥75%	≥0.5	280	50	14.9	39*22*19
	PVA-24040M003	200*33*23	100-240	40	1.66A	24±5%	≥75%	≥0.5	280	50	14.9	39*22*19
	PVA-12060M004	150*68*48	100-240	60	5A	12±5%	≥80%	≥0.5	680	20	13.6	38.2*34.2*20
	PVA-24060M004	150*68*48	100-240	60	2.5A	24±5%	≥80%	≥0.5	680	20	13.6	38.2*34.2*20
	PVA-12100M005	200*75*45	110-240	100	8.3A	12±5%	≥80%	≥0.5	1000	20	22.4	41.8*23*26.5
	PVA-24100M005	200*75*45	110-240	100	4.2A	24±5%	≥80%	≥0.5	1000	20	22.4	41.8*23*26.5
	PVA-12150M006	230*75*45	110-240	150	12.5A	12±5%	≥80%	≥0.5	1200	20	23.6	41.8*25*26.5
	PVA-24150M006	230*75*45	110-240	150	6.25A	24±5%	≥80%	≥0.5	1200	20	23.6	41.8*25*26.5
	PVA-12200M007	238*131*60	175-250	200	16.67A	12±5%	≥80%	≥0.5	2400	5	12	44.5*30.2*19
	PVA-24200M007	238*131*60	175-250	200	8.33A	24±5%	≥80%	≥0.5	2400	5	12	44.5*30.2*19



NPOWER PRODUCTS LIST 产品目录

PRODUCT PHOTO 产品图片	PRODUCT MODEL 产品型号	PRODUCT SIZE 产品尺寸 (MM)	INPUT AC 输入电压 (V)	OUTPUT POWER 输出功率 (W)	OUTPUT CURRENT 输出电流 (MA)	OUTPUT VOLTAGE 输出电压 (V)	Efficiency 效率	PFC 功率因数	Unit Weight 单重 (G)	QTY/BOX 数量/箱	KG/BOX KG/箱	BOX SIZE 外箱尺寸 (CM)
-----------------------	-----------------------	---------------------------	----------------------	--------------------------	-----------------------------	----------------------------	------------------	-------------	-----------------------	-----------------	----------------	-----------------------

Waterproof LED Driver-----Constant Current 恒流大功率防水电源

	PAA-12300M009	φ 25*22	100-240	3.6	300±5%	2-12	≥80%	≥0.5	28	800	19.6	38.2*34.2*19.6
	PAA-04700M009	φ 25*22	100-240	2.88	700±5%	2-4	≥80%	≥0.5	28	800	19.6	38.2*34.2*19.6
	PAA-12300P003	50*27*22	100-240	3.6	300±5%	2-12	≥80%	≥0.5	26	500	13.3	38.2*34.2*19.6
	PAA-04700P003	50*27*22	90-264	2.88	700±5%	2-4	≥80%	≥0.5	26	500	13.3	38.2*34.2*19.6
	PDC-04700P003	50*27*22	12-24	2.88	700±5%	2-4	≥80%	≥0.5	26	500	13.3	38.2*34.2*19.6
	PAA-28300P038	35*31*21	100-240	8.96	300±5%	12-25	≥80%	≥0.5	28	350	13.3	38.2*34.2*19.6
	PAA-28300P004	76*38*28	100-240	8.96	300±5%	12-28	≥80%	≥0.5	80	50	12	39*22*19
	PAA-12700P004	76*38*28	100-240	8.64	700±5%	5-12	≥80%	≥0.5	200	50	12	39*22*19
	PAA-36300M001	160*25*22	100-240	11.52	320±5%	20-36	≥80%	≥0.5	180	50	9.4	39*22*19
	PAA-50300M001	160*25*22	100-240	16	320±5%	34-50	≥80%	≥0.5	180	50	9.4	39*22*19
	PAA-36520M001	160*25*22	100-240	19.8	520±5%	20-36	≥80%	≥0.5	180	50	9.4	39*22*19
	PAA-12900M001	160*25*22	100-240	11.16	900±5%	2-12	≥80%	≥0.5	180	50	9.4	39*22*19
	PAA-121400M001	160*25*22	100-240	16.8	1400±5%	2-12	≥80%	≥0.5	180	50	9.4	39*22*19
	PAA-24700M001	160*25*22	100-240	16.8	700±5%	12-24	≥80%	≥0.5	180	50	9.4	39*22*19
	PAA-70300M002	200*30*20	100-240	21	320±5%	42-70	≥80%	≥0.5	220	50	11.5	41.5*23.5*15.2
	PAA-90300M002	200*30*20	100-240	27	320±5%	50-85	≥80%	≥0.5	220	50	11.5	41.5*23.5*15.2
	PAA-36700M002	200*30*20	100-240	25.2	700±5%	20-36	≥80%	≥0.5	220	50	11.5	41.5*23.5*15.2
	PAA-22900M002	200*30*20	100-240	20.245	900±5%	8-22	≥80%	≥0.5	220	50	11.5	41.5*23.5*15.2
	PAA-48700M002	200*30*20	100-240	33.6	700±5%	30-52	≥80%	≥0.5	220	50	11.5	41.5*23.5*15.2
	PAA-241000M002	200*30*20	100-240	24	1000±5%	12-24	≥80%	≥0.5	220	50	11.5	41.5*23.5*15.2
	PAA-36900M003	200*35*22	100-240	32.4	900±5%	20-36	≥80%	≥0.5	280	50	14.9	39*22*19
	PAA-241400M003	200*33*23	100-240	33.6	1400±5%	12-24	≥80%	≥0.5	280	50	14.9	39*22*19
	PAA-50550M003	200*33*23	100-240	27.5	550±5%	30-52	≥80%	≥0.5	280	50	14.9	39*22*19
	PAA-60520M003	200*33*23	100-240	31.2	520±5%	40-60	≥80%	≥0.5	280	50	14.9	39*22*19
	PAA-36520M013	110*60*28	100-240	18.7	520±5%	20-36	≥80%	≥0.5	270	50	13.7	39*22*19
	PAA-36900M013	110*60*28	100-240	32.4	900±5%	20-36	≥80%	≥0.5	270	50	13.7	39*22*19
	PAA-70300M013	110*60*28	100-240	21	700±5%	42-70	≥80%	≥0.5	270	50	13.7	39*22*19
	PAA-90700M004	150*75*45	100-240	63	700±5%	50-85	≥80%	≥0.5	680	20	13.6	38.2*34.2*20
	PAA-381440M004	150*75*45	100-240	54.7	1440±5%	20-36	≥80%	≥0.5	680	20	13.6	38.2*34.2*20



NPOWER PRODUCTS LIST 产品目录

PRODUCT PHOTO 产品图片	PRODUCT MODEL 产品型号	PRODUCT SIZE 产品尺寸 (MM)	INPUT AC 输入电压 (V)	OUTPUT POWER 输出功率 (W)	OUTPUT CURRENT 输出电流 (MA)	OUTPUT VOLTAGE 输出电压 (V)	Efficiency 效率	PFC 功率因数	Unit Weight 单重 (G)	QTY/BOX 数量/箱	KG/BOX KG/箱	BOX SIZE 外箱尺寸 (CM)
Waterproof LED Driver-----High Power Factor Constant Voltage 高功率因数恒压防水电源												
	PVA-12060PFC	175*75*45	100-240	60	5A	12±5%	≥80%	≥0.9	855	20	17.1	42*38*20.5
	PVA-24060PFC	150*68*50	100-240	60	3A	24±5%	≥80%	≥0.9	855	20	17.1	42*38*20.5
	PVA-12100PFC	200*75*45	170-240	100	8A	12±5%	≥80%	≥0.9	1000	20	22.4	41.8*23*26.5
	PVA-24100PFC	200*75*45	170-240	100	4A	24±5%	≥80%	≥0.9	1000	20	22.4	41.8*23*26.5
	PVA-12150PFC	235*75*45	170-240	150	8A	12±5%	≥80%	≥0.9	1200	20	23.6	41.8*25*26.5
	PVA-24150PFC	235*75*45	170-240	150	4A	24±5%	≥80%	≥0.9	1200	20	23.6	41.8*25*26.5
Waterproof LED Driver-----High Power Factor Constant Current with Aluminium Alloy Cover 高功率因数恒流防水电源												
	PAA-48700PFC	160*75*45	100-240	33.6	700±5%	30-45	≥85%	≥0.95	855	20	17.1	42*38*20.5
	PAA-362400PFC	200*75*45	100-240	86.4	2400±5%	20-36	≥85%	≥0.95	1000	20	22.4	41.8*23*26.5
	PAA-363000PFC	200*75*45	100-240	108	3000±5%	20-36	≥85%	≥0.95	1000	20	22.4	41.8*23*26.5
Non-Waterproof LED Driver-----High Power Factor Constant Current with Plastic Cover 高功率因素塑胶外壳恒流电源												
	PAA-40150PFC	80*32*21	100-240	6	150±5%	24-40	≥70%	≥0.9	13.5			
	PAA-18300PFC	80*32*21	100-240	5.4	300±5%	4-18	≥70%	≥0.9	13.5			
	PAA-10500PFC	80*32*21	100-240	5	500±5%	2-10	≥70%	≥0.9	13.5			
	PAA-56150PFC	94*45*27	100-240	8.4	150±5%	40-56	≥70%	≥0.9	13.5			
	PAA-28320PFC	94*45*27	100-240	8.96	320±5%	12-28	≥70%	≥0.9	13.5			
	PAA-16500PFC	94*45*27	100-240	8	500±5%	4-16	≥70%	≥0.9	13.5			
	PAA-48300PFC	94*45*27	100-240	14.4	300±5%	32-48	≥70%	≥0.9	22.5			
	PAA-30500PFC	94*45*27	100-240	15	500±5%	14-30	≥70%	≥0.9	22.5			
	PAA-80300PFC	115*45*27	100-240	24	300±5%	64-80	≥70%	≥0.9	51.6			
	PAA-36700PFC	115*45*27	100-240	25.2	700±5%	20-36	≥70%	≥0.9	51.6			
	PAA-28900PFC	115*45*27	100-240	25.2	900±5%	12-28	≥70%	≥0.9	95			
	PAA-80500PFC	150*45*28	100-240	40	500±5%	64-80	≥70%	≥0.9	120			
	PAA-48700PFC	150*45*28	100-240	33.6	700±5%	32-48	≥70%	≥0.9	120			
	PAA-50960PFC	150*45*28	100-240	48	960±5%	34-50	≥70%	≥0.9	120			
	PAA-361500PFC	150*45*28	100-240	54	1500±5%	20-36	≥70%	≥0.9	120			



NPOWER PRODUCTS LIST 产品目录

PRODUCT PHOTO 产品图片	PRODUCT MODEL 产品型号	PRODUCT SIZE 产品尺寸 (MM)	INPUT AC 输入电压 (V)	OUTPUT POWER 输出功率 (W)	OUTPUT CURRENT 输出电流 (MA)	OUTPUT VOLTAGE 输出电压 (V)	Efficiency 效率	PFC 功率因数	Unit Weight 重量 (G)	QTY/BOX 数量/箱	KG/BOX KG/箱	BOX SIZE 外箱尺寸 (CM)
-----------------------	-----------------------	---------------------------	----------------------	--------------------------	-----------------------------	----------------------------	------------------	-------------	-----------------------	-----------------	----------------	-----------------------

Non-Waterproof LED Driver-----High Power Factor Constant Current for LED Flood Light 投光灯电源

	PAA-80300PFC-N	85*38*25	100-240	24	300±5%	64-80	≥70%	≥0.9	50			
	PAA-36700PFC-N	85*38*25	100-240	25	500±5%	34-50	≥70%	≥0.9	50			
	PAA-28900PFC-N	85*38*25	100-240	25.2	700±5%	20-36	≥70%	≥0.9	50			
	PAA-50WLP8-10X4	108*29*28	100-240	40.8	1.2A±5%	24-34	≥85%	≥0.9	55			
	PAA-50WLP8-10X5	108*29*28	100-240	51	1.5A±5%	24-34	≥85%	≥0.9	55			
	PAA-50WLP12-18X3	108*29*28	100-240	50.4	900±5%	36-56	≥85%	≥0.9	55			
	PAA-50WLP12-21X3	108*29*28	100-240	42	630±5%	40-70	≥85%	≥0.9	55			
	PAA-362400PFC-N	160*80*40	100-240	86.4	2400±5%	20-36	≥85%	≥0.95	750	20	16.5	41.8*23*26.5
	PAA-363000PFC-N	160*80*40	100-240	108	3000±5%	20-36	≥85%	≥0.95	750	20	22.4	41.8*23*26.5

Non-Waterproof LED Driver-----High Power Factor Constant Current for LED Tube 日光灯电源

	PAA-T8-GY-F 2808	210*17*11	100-240	24	460±5%	30-52	≥85%	≥0.85	44	120	4	the voltage & current could be adjusted within this power range
	PAA-CE-T8-F 2808B	265*17*11	100-240	25	450±5%	30-52	≥85%	≥0.85	32	120	4	the voltage & current could be adjusted within this power range
	PAA-T8-F 2808	210*17*11	100-240	24	460±5%	30-52	≥85%	≥0.85	21	120	4	the voltage & current could be adjusted within this power range
	PAA-T8-F 9853OB	185*17*11	100-240	18	220±5%	30-80	≥90%	≥0.9	20	120	4	the voltage & current could be adjusted within this power range
	PAA--T8-GL 3309	250*17*11	100-240	30	550±5%	30-90	≥80%	≥0.93	32	120	4	the voltage & current could be adjusted within this power range
	PAA-T8-TG 2808	225*17*11	100-240	24	460±5%	60-90	≥85%	≥0.85	67	120	4	the voltage & current could be adjusted within this power range



NPOWER PRODUCTS LIST 产品目录

PRODUCT PHOTO 产品图片	PRODUCT MODEL 产品型号	PRODUCT SIZE 产品尺寸 (MM)	INPUT AC 输入电压 (V)	OUTPUT POWER 输出功率 (W)	OUTPUT CURRENT 输出电流 (MA)	OUTPUT VOLTAGE 输出电压 (V)	Efficiency 效率	PFC 功率因数	Unit Weight 单重 (G)	QTY/BOX 数量/箱	KG/BOX KG/箱	BOX SIZE 外箱尺寸 (CM)
Non-Waterproof LED Driver-----Constant Current for LED Bulb, PAR Light 球泡灯, PAR灯电源												
	PAA-40150PFC	50*16*18	100-240	6	150±5%	24-40	≥70%	≥0.9	12.2			
	PAA-18300PFC	50*16*18	100-240	5.4	300±5%	4-18	≥70%	≥0.9	12.2			
	PAA-10500PFC	50*16*18	100-240	5	500±5%	2-10	≥70%	≥0.9	12.2			
	PAA-56150PFC	55*20*18	100-240	8.4	150±5%	40-56	≥80%	≥0.9	20.2			
	PAA-28320PFC	55*20*18	100-240	8.96	320±5%	12-28	≥80%	≥0.9	20.2			
	PAA-16500PFC	55*20*18	100-240	8	500±5%	4-16	≥80%	≥0.9	20.2			
	PAA-90150PFC	65*25*15	100-240	13.5	150±5%	74-90	≥80%	≥0.9	29.6			
	PAA-48300PFC	65*25*15	100-240	14.4	300±5%	32-48	≥80%	≥0.9	29.6			
	PAA-30500PFC	65*25*15	100-240	15	500±5%	14-30	≥80%	≥0.9	29.6			
	PAA-PF- (4-9W) 3309	48*21*17	100-240	9	300±5%	12-32	≥86%	≥0.9	12			
	PAA-PF- (10-18W) 3309	53*21*19	100-240	18	300±5%	30-63	≥80%	≥0.9	12			
	PAA-18WLP9-18X1	53*21*21	100-240	18	300±5%	40-60	≥85%	≥0.9	20			
	PAA-18WLP5-9X3	53*21*21	100-240	18	630±5%	15-30	≥85%	≥0.9	20			
	PAA-18WLP3-5X3	53*21*21	100-240	14.4	900±5%	9-16	≥85%	≥0.9	20			
	PAA-GU010- (1-3) /1W	24*16.5*16	100-240	4	300±5%	3-14	≥80%	≥0.6	10			
	PAA-GU010-1/3W	24*16.5*16	100-240	3	700±5%	2-4	≥80%	≥0.6	10			
	PAA-PART- (4-7) /1W	29*26*17	100-240	7	300±5%	9-28	≥80%	≥0.6	11			Max current:550ma
	PAA-PART- (5-9) /1W	40*17*18	100-240	9	300±5%	16-32	≥80%	≥0.6	11			Max current:400ma
	PAA-PART- (8-15) /1W	53*20*15	100-240	15	300±5%	24-52	≥80%	≥0.6	16			Max current:450ma
	PAA-PART- (10-18) /1W	53*21*20	100-240	18	300±5%	30-60	≥80%	≥0.6	20			
	PAA-PART- (3-6) /3W	53*21*20	100-240	18	700±5%	9-24	≥80%	≥0.6	20			



NPOWER PRODUCTS LIST 产品目录











PRODUCT PHOTO 产品图片	PRODUCT MODEL 产品型号	PRODUCT SIZE 产品尺寸 (MM)	INPUT AC 输入电压 (V)	OUTPUT POWER 输出功率 (W)	OUTPUT CURRENT 输出电流 (MA)	OUTPUT VOLTAGE 输出电压 (V)	Efficiency 效率	PFC 功率因数	Unit Weight 单重 (G)	QTY/BOX 数量/箱	KG/BOX KG/箱	BOX SIZE 外箱尺寸 (CM)
Non-Waterproof LED Driver-----Dimmable 调光电源												
	PAA-20130-TG	17* (14+8)	100-240	3	120±15	16-20	≥65%	≥0.5	23			
	PAA-TG- (4-15) /1W	39*17*17	100-240	15	300±5%	12-52	≥80%	≥0.6	45			
Rainproof LED Power Supply-----Constant Voltage 恒压防雨开关电源												
	PVA-12060G-FY	155*105*47	100-240	60	5A	12±5%	≥80%	≥0.5	500	30	16.5	46.3×32.3×25.4
	PVA-24060G-FY	155*105*47	100-240	60	2.5A	24±5%	≥80%	≥0.5	500	30	16.5	46.3×32.3×25.4
	PVA-12100G-FY	195*112*50	100/220	100	8.3A	12±5%	≥80%	≥0.5	760	20	16.7	46.3×32.3×25.4
	PVA-24100G-FY	158*98*38	100/220	100	4.2A	24±5%	≥80%	≥0.5	760	20	16.7	46.3×32.3×25.4
	PVA-12120G-FY	158*98*38	100/220	120	10A	12±5%	≥80%	≥0.5	760	20	16.7	46.3×32.3×25.4
	PVA-24120G-FY	158*98*38	100/220	120	5A	24±5%	≥80%	≥0.5	760	20	16.7	46.3×32.3×25.4
	PVA-12150G-FY	225*105*50	100/220	150	12.5A	12±5%	≥80%	≥0.5	760	20	16.7	46.3×32.3×25.4
	PVA-24150G-FY	225*105*50	100/220	150	6.25A	24±5%	≥80%	≥0.5	760	20	16.7	46.3×32.3×25.4
	PVA-12200G-FY	225*105*50	170-264	200	16.5A	12±5%	≥80%	≥0.5	1100	15	18	45×27.8×37.8
	PVA-24200G-FY	225*105*50	170-264	200	8.25A	24±5%	≥80%	≥0.5	1100	15	18	45×27.8×37.8
	PVA-12250G-FY	230*120*60	170-264	250	21A	12±5%	≥80%	≥0.5	1100	15	18	45×27.8×37.8
	PVA-24250G-FY	230*120*60	170-264	250	10.5A	24±5%	≥80%	≥0.5	1100	15	18	45×27.8×37.8
	PVA-12300G-FY	230*120*60	170-264	300	25A	12±5%	≥80%	≥0.5	1100	15	18	45×27.8×37.8
	PVA-24300G-FY	230*120*60	170-264	300	12.5A	24±5%	≥80%	≥0.5	1100	15	18	45×27.8×37.8
	PVA-12350G-FY	255*140*65	170-264	350	29A	12±5%	≥80%	≥0.5	1300	15	21	45×27.8×37.8
	PVA-24350G-FY	255*140*65	170-264	350	14.5A	24±5%	≥80%	≥0.5	1300	15	21	45×27.8×37.8
	PVA-12250G-PFC	230*120*60	170-264	250	21A	12±5%	≥80%	≥0.5	1100	15	18	45×27.8×37.8
	PVA-12350G-PFC	255*140*65	170-264	350	29A	12±5%	≥80%	≥0.5	1300	15	21	45×27.8×37.8



NPOWER PRODUCTS LIST 产品目录

PRODUCT PHOTO 产品图片	PRODUCT MODEL 产品型号	PRODUCT SIZE 产品尺寸 (MM)	INPUT AC 输入电压 (V)	OUTPUT POWER 输出功率 (W)	OUTPUT CURRENT 输出电流 (MA)	OUTPUT VOLTAGE 输出电压 (V)	Efficiency 效率	PFC 功率因数	Unit Weight 单重 (G)	QTY/BOX 数量/箱	KG/BOX KG/箱	BOX SIZE 外箱尺寸 (CM)
-----------------------	-----------------------	---------------------------	----------------------	--------------------------	-----------------------------	----------------------------	------------------	-------------	-----------------------	-----------------	----------------	-----------------------

Switching Power Supply-----Constant Voltage 恒压开关电源

	PVA-05015G	78*48*22	100-240	15	3A	5±5%	≥75%	≥0.5	100	300	22.5	46.3*32.3*25.4
	PVA-12015G	78*48*22	100-240	15	1.25A	12±5%	≥75%	≥0.5	100	300	22.5	46.3*32.3*25.4
	PVA-24015G	78*48*22	100-240	15	0.625A	24±5%	≥75%	≥0.5	100	300	22.5	46.3*32.3*25.4
	PVA-05030G	85*58*38	100-240	35	7A	5±5%	≥75%	≥0.5	180	150	26	46.3*32.3*25.4
	PVA-12030G	85*58*38	100-240	35	2.9A	12±5%	≥75%	≥0.5	180	150	26	46.3*32.3*25.4
	PVA-24030G	85*58*38	100-240	35	1.46A	24±5%	≥75%	≥0.5	180	150	26	46.3*32.3*25.4
	PVA-05060G	110*78*38	100-240	60	12A	5±5%	≥75%	≥0.5	290	80	24.4	43.8*33.5*25
	PVA-12060G	110*78*38	100-240	60	5A	12±5%	≥75%	≥0.5	290	80	24.4	43.8*33.5*25
	PVA-24060G	110*78*38	100-240	60	2.5A	24±5%	≥80%	≥0.5	290	80	24.4	43.8*33.5*25
	PVA-05100G	158*98*38	100/220	100	20A	5±5%	≥80%	≥0.5	500	40	20.5	43.8*33.5*25
	PVA-12100G	158*98*38	100/220	100	8.3A	12±5%	≥80%	≥0.5	500	40	20.5	43.8*33.5*25
	PVA-24100G	158*98*38	100/220	100	4.2A	24±5%	≥80%	≥0.5	500	40	20.5	43.8*33.5*25
	PVA-05120G	158*98*38	100/220	120	24A	5±5%	≥80%	≥0.5	500	40	20.5	43.8*33.5*25
	PVA-12120G	158*98*38	100/220	120	10A	12±5%	≥80%	≥0.5	500	40	20.5	43.8*33.5*25
	PVA-24120G	158*98*38	100/220	120	5A	24±5%	≥80%	≥0.5	500	40	20.5	43.8*33.5*25
	PVA-05150G	199*98*38	100/220	150	30A	5±5%	≥80%	≥0.5	650	30	16.7	43.8*33.5*25
	PVA-12150G	199*98*38	100/220	150	12.5A	12±5%	≥80%	≥0.5	650	30	16.7	43.8*33.5*25
	PVA-24150G	199*98*38	100/220	150	6.25A	24±5%	≥80%	≥0.5	650	30	16.7	43.8*33.5*25
	PVA-05200G	200*110*50	100/220	200	40A	5±5%	≥80%	≥0.5	700	24	17	43.8*33.5*25
	PVA-12200G	200*110*50	100/220	200	16.5A	12±5%	≥80%	≥0.5	700	24	17	43.8*33.5*25
	PVA-24200G	200*110*50	100/220	200	8.25A	24±5%	≥80%	≥0.5	700	24	17	43.8*33.5*25
	PVA-05250G	200*110*50	100/220	250	50A	5±5%	≥80%	≥0.5	730	24	18	43.8*33.5*25
	PVA-12250G	200*110*50	100/220	250	21A	12±5%	≥80%	≥0.5	730	24	18	43.8*33.5*25
	PVA-24250G	200*110*50	100/220	250	10.5A	24±5%	≥80%	≥0.5	750	24	18	43.8*33.5*25
	PVA-12300G	200*110*50	100/220	300	25A	12±5%	≥80%	≥0.5	750	24	18.5	43.8*33.5*25
	PVA-24300G	200*110*50	100/220	300	12.5A	24±5%	≥80%	≥0.5	750	24	18.5	43.8*33.5*25
	PVA-12350G	240*125*60	100/220	350	29A	12±5%	≥80%	≥0.5	1500	10	16	47.5*29.8*18.5
	PVA-24350G	240*125*60	100/220	350	14.5A	24±5%	≥80%	≥0.5	1500	10	16	47.5*29.8*18.5
	PVA-12400G	240*125*60	100/220	400	33A	12±5%	≥80%	≥0.5	1500	10	16	47.5*29.8*18.5
	PVA-24400G	240*125*60	100/220	400	16.5A	24±5%	≥80%	≥0.5	1500	10	16	47.5*29.8*18.5